



Longarm Quilting Intake Form

Name: _____

Address: _____

Phone: _____ Email: _____

Requested Completion Date: _____ Completion Date: _____

Quilt Top - Width: _____ Length: _____

Batting - Width: _____ Length: _____ Type: _____

Backing - Width: _____ Length: _____ Type: _____

Edge 2 Edge Quilt Design: _____

Thread Preference: _____

Special Instructions/Notes:

Costs:

Quilting: _____ square inches x \$_____ = _____ (Min: \$60.00)

*Batting: _____ width x \$_____/meter = _____ (Hobbs 80/20)

*Backing: _____ width x _____/meter = _____

Subtotal = _____

Tax = _____

Total = _____

I agree to the specifications above and authorize FibreChick to proceed with the quilting of my quilt top. I understand quilting involves uncontrollable elements and best efforts will be made to produce a quality quilted product.

Signature: _____ Date: _____

*Supply your own batting/backing or receive 15% off the purchase of in-shop batting/backing (before tax) on quilts quilted by the FibreChick shop.

**Thread intensive patterns and large quilts require more thread time! There will be an additional charge if larger and have a thread intensive pattern.

At the FibreChick Shop our specialty is all-over edge-to-edge machine quilting. In other words, the same pattern will be repeated over the entire quilt.

PREPARE your quilt for longarm quilting.

NOTE:

- Quilts must be clean and free of strong odors.
- Quilting does not correct piecing problems. If there is fullness in the center or wavy borders, you may end up with puckers and pleats. To avoid wavy borders and pleats, make your quilt fit your borders by measuring through the center of the quilt and cut your borders to that length. When you sew the borders, you may need to ease the quilt to fit the borders.
- **DO NOT BASTE** the quilt layers together. All layers need to be separate and will be attached separately on the machine.

COMPLETE your quilt top

- **CLIP** all hanging threads as thread will show through the quilt top.
- **STITCH 1/8"** around the perimeter of the quilt, so pieced seams will not come loose and wiggle apart.
- **PRESS**, so your quilt top and sewn seams are flat.
- **CUT** curved corners after the machine quilting is completed.
- **IDENTIFY** the top of your quilt with a safety pin. Mainly for directional prints on quilts.
- **TOPSTITCH** any loose applique elements to the quilt. Embellishments, buttons, beads, etc., should be added to the quilt **AFTER** the longarm machine quilting is completed.

PREPARE your backing and batting

- **PURCHASE OR PROVIDE** backing and batting 8" wider and 8" longer than the quilt top.
- **100%** quilting cotton or cotton flannel backing comparable to your finished quilt top is preferred.
- **SEW** a 5/8" seam, if you are piecing a backing. **PRESS** the seam open.
- **PRESS** the backing flat.

CALCULATE the approximate cost of quilting your quilt:

Quilt Width x Quilt Length x .02 = \$ _____ (plus, batting & backing)
(Minimum \$60.00)

Batting (80/20) Hobbs

- \$17/Meter - 96" Width
- \$20/Meter - 120" Width

Quilting up to

100k Stitches - \$0.02/Square Inch (Approx. 76"x76")

**100k-150k Stitches - \$0.025/Square Inch (Approx. 76"x90")

**Over 150k Stitches - \$0.03/Square Inch (Approx. 92"x92")